

# Line Coupler

KNX

The LC00B01KNX KNX line coupler has been made in a compact design. It connects two KNX bus segments (for example, a KNX line with a KNX area). The device has a filter table (8k bytes) and ensures a galvanic isolation between the lines. The coupler supports KNX long frames and is compatible with the ETS® software (ETS 4.2 or higher).

The buttons on the front panel allow disabling the telegram filter for testing purposes. The LEDs indicate operating conditions as well as communication errors on the KNX bus.



## Technical Features

<b>Mechanical data</b>	<ul style="list-style-type: none"> <li>• Dimensions: 1 DIN Modules</li> </ul>
<b>Supply</b>	<ul style="list-style-type: none"> <li>• Via bus EIB/KNX cable: 21 ÷ 32 Vdc</li> </ul>

## Order Codes

**LC00B01KNX**  
Line Coupler KNX

# USB-KNX

INTERFACE

The device enables the KNX bus system to be interfaced to a PC equipped with a port for programming or managing through appropriate software.



## Technical Features

<b>Mechanical data</b>	<ul style="list-style-type: none"> <li>• Dimensions: 1 DIN Modules</li> </ul>
<b>Supply</b>	<ul style="list-style-type: none"> <li>• Via bus EIB/KNX cable: 21 ÷ 32 Vdc</li> <li>• USB consumption: &lt; 15 mA</li> </ul>
<b>USB Connection</b>	<ul style="list-style-type: none"> <li>• Connector type B</li> <li>• Max. cable length: 5 m</li> </ul>

## Order Codes

**IN00A03USB**  
USB-KNX Interface